
## Features


- ★Good aluminum alloy heat sink with good quality heat dissipation, high
- ★High quality constant current driver-Mean Well, both to ensure the stability of the product, but also greatly reduce the power consumption.
- ★Adoping Epistar or Birdgelux integrated chip ,antiglare.
- ★Constant voltage, constant current. Over voltage \ over power \ over current protection, lighting protection.
- ★Start up within 1`3 seconds, no flicker, anti-jamming, no mercury, energy saving, environment friendly.




## Distribution Chart




Size





Intensity of illumination



## Technical Parameters


Item No.	WL-BR-HB-010
Input Voltage	AC 100-240V 50/60Hz
Working Voltage	DC 30-36V
Power Factor	>0.95
LEDs	1PCS
Power Consumption	35W
Luminous Flux	>2700lm
Color Temperature	3000K/4500K/6000K
CRI	Ra>70
Beam Angle	45° 90° 120°
Working Temperature	-25℃+45℃
Working Humidity	10%-90% RH
Keeping Temperature	-40℃+65℃
Lifespan	≥50000H
Material	6063AL+lens
Heatsink	D160*H65mm
Packing Size	250*250*245mm
Net Weight	4.4KG
IP class	IP65

## Application

★Factories,workshops,warehouses,exhibition centers,shopping malls or supermarkets, stadiums, toll stations, etc.



Angle Reflector



Willighting(ShenZhen) Co.,Ltd

Add: 6F E Building of Hong Rongfa Industry Area, No. 460 Xiang Shan Rd, Luotian Songgang,
Shenzhen, Guangdong, China
Tel:+86-755-27649783 - sales @willighting.com www.willighting.com