
Features


- $\bigstar \mbox{Good aluminum alloy heat sink with good quality heat dissipation, high strength.}$
- ★High quality constant current driver-Mean Well, both to ensure the stability of the product, but also greatly reduce the power consumption.
- ★Adoping Epistar or Birdgelux integrated chip ,antiglare.
- ★Constant voltage, constant current. Over voltage \ over power \ over current protection, lighting protection.
- ★Start up within 1`3 seconds, no flicker, anti-jamming, no mercury, energy saving, environment friendly.




Distribution Chart







Intensity of illumination



Technical Parameters


Item No.	WL-BR-HB-017
Input Voltage	AC 90-295V 50/60Hz
Working Voltage	DC 30-36V
Power Factor	>0.9
LEDs	3PCS*80W
Power Consumption	240W
Luminous Flux	>22000lm
Color Temperature	3000K/4500K/6000K
CRI	Ra>70
Beam Angle	45°90°120°
Working Temperature	-25℃+45℃
Working Humidity	10%-90% RH
Keeping Temperature	-40℃+65℃
Lifespan	≥50000H
Material	6063AL+lens
Heatsink	D280*H280mm
Packing Size	310*310*490mm
Net Weight	8.3KG
IP class	IP65

Application

★Factories,workshops,warehouses,exhibition centers,shopping malls or supermarkets,stadiums,toll stations, etc.



Angle Reflector



fake comfortable