

Features

- ★Good aluminum alloy heat sink with good quality heat dissipation, high strength.
- ★High quality constant current driver-Mean Well, both to ensure the stability of the product, but also greatly reduce the power consumption.
- ★Adoping Epistar or Birdgelux integrated chip ,antiglare.
- \bigstar Constant voltage, constant current. Over voltage \ over power \ over current protection, lighting protection.
- ★Start up within 1 3 seconds, no flicker, anti-jamming, no mercury, energy saving, environment friendly.




Distribution Chart





Intensity of illumination



Technical Parameters


Item No.	WL- BR-HB-012
Input Voltage	AC 100-240V 50/60Hz
Working Voltage	DC 30-36V
Power Factor	>0.9
LEDs	1PCS
Power Consumption	85W
Luminous Flux	>75001m
Color Temperature	3000K/4500K/6000K
CRI	Ra>70
Beam Angle	45°90°120°
Working Temperature	-25℃+45℃
Working Humidity	10%-90% RH
Keeping Temperature	-40℃+65℃
Lifespan	≥50000H
Material	6063AL+lens
Heatsink	D160*H135mm
Packing Size	250*250*315mm
Net Weight	5.38KG
IP class	IP65

Application

★Factories,workshops,warehouses,exhibition centers,shopping malls or supermarkets,stadiums,toll stations, etc.



Angle Reflector



Make comfortable

Willighting(ShenZhen) Co.,Ltd Add: 6F E Building of Hong Rongfa Industry Area, No. 460 Xiang Shan Rd, Luotian Songgang, Shenzhen, Guangdong, China Tel:+86-755-27649783 sales@willighting.com www.willighting.com